



NOTES

1. A Consent to erect a structure on Road Reserve is required from the Council.
 2. A Building Consent is required for Foot Bridges across Streams.
 3. An ARC Consent may be required when working adjacent to Stream.
 4. A Consent to remove Trees / Work in Dripline must be obtained from the Council.
 5. The ATV Accessway Route / Alignment must be approved by the Council prior to work commencing.
- A Safety Platform must be installed where it meets a Public Road. See ACC Standard Engineering Detail No. 2008/0618.
6. Retaining Walls less than 1m high shall be constructed in accordance with ACC Standard Engineering Detail No. 2008/0418.
 7. The Minimum Horizontal Curve shall be 5.0m or as directed by the Engineer.
 8. The preferred Grade is 1 in 6 with the absolute maximum Gradient of 1 in 3. Gradients steeper than 1 in 4 will require specific design.
 9. A Cut Off Drain shall be installed at 30–50m intervals or as directed by the Engineer.

PREPARED BY OPUS:



AUCKLAND CITY
Transport

TYPICAL CROSS SECTION
DETAIL – ATV
ACCESSWAY

SCALE : NTS

DRAWN : MKG

ISSUE DATE : 11/2008

APPROVED :

PLAN No. ISSUE B

2008/0625