



<u>PAVING TYPE A</u>

BASALT FLAGSTONES 900 x 450 x 40MM THICK BASALT G3027 (FLAMED FINISH)



PAVING TYPE B

BASALT FLAGSTONES 672 x 450 x 40MM THICK BASALT G3027 (FLAMED FINISH)




PAVING TYPE C

INSETS

225 x 450 x 40MM THICK


GRANITE G654

(FLAMED FINISH)



PAVING TYPE D

ETCHED INSETS
225 x 450 x 40MM THICK
GRANITE G654
(SAND BLASTED/ETCHED
FINISH)




PAVING TYPE E

HERITAGE MAT PAVERS

150 x RANDOM LENGTH* x 40MM THICK
RECYCLED AUCKLAND BASALT
KERBSTONES OR SELECTED STONE
(FINISHED TO BE SELECTED)

* RANDOM LENGTH 300MM MIN.



PAVING TYPE F

MACALLUMS PAVERS
600 x 300 x 60MM THICK
RECYCLED MACALLUMS CHIP
PAVERS
(HONED FINISH)

PREPARED BY OPUS:



AUCKLAND CITY

Transport

QUEEN STREET
PAVING AND KERB TYPES
SHEET ONE OF FIVE

SCALE: NTS

DRAWN: MKG

ISSUE DATE : 11/2008

APPROVED :

PLAN No. ISSUE B